CITY OF NAPLES PURCHASING DIVISION CITY HALL, 735 8TH STREET SOUTH NAPLES, FLORIDA 34102

PH: 239-213-7100 FX: 239-213-7105

ADDENDUM NUMBER 2

NOTIFICATION DATE:	BID TITLE:	BID NUMBER:	BID OPENING DATE & TIME:	
12/05/12	Pavement Management Services	009-12	01/11/12 2:00PM	

THE FOLLOWING INFORMATION IS HEREBY INCORPORATED INTO, AND MADE AN OFFICIAL PART OF THE ABOVE REFERENCED BID.

Please replace Section F-Pavement Markings of the Compensation Schedule with the following: The original contained error. This is found on pages 50-51. Please use these corrected pages when submitting your proposal

<u>Section F – Pavement Markings:</u>

I. PAINT

1. Contractor to provide labor, equipment and materials for 15 mil reflective roadway paint and required glass beads to be applied on various roadways. The min. wet film thickness for painted areas is 15 mils

•	Lines 15 mils						
a.	6"	Under one (1) mile	LF	\$			
		Over one (1) mile	LF	\$			
b.	8"	15 mils	LF	\$			
C.	12"	15 mils	LF	\$			
d.	18"	15 mils	LF	\$			
e.	24"	15 mils	LF	\$			

•	Symbols and Pavement Messages 15 mil					
a.	Miscellaneous Paint	SF	\$			

SUBTOTAL SECTION I:	\$
SUBTOTAL SECTION I.	Ψ

II. THERMOPLASTIC

- Contractor to provide labor, equipment and materials for thermoplastic markings to be applied on various roadways and/or intersections, to include symbols and pavement messages. The min. wet film thickness for thermoplastic areas is either 60 mils or 90 mils
- 2. Thermoplastic markings to be applied on various roadways may include edge lines, centerlines, stop bars, crosswalks lanes, and bike paths.

	60 mil		, , , , , , , , , , , , , , , , , , ,		
a	6"	Under one (1) mile	LF	\$	
		Over one (1) mile	LF	\$	
).	8"	60 mils	LF	\$	
C.	12"	60 mils	LF	\$	
d.	18"	60 mils	LF	\$	
е.	24"	60 mils	LF	\$	
•	90 mil	<u> </u>			
a.	6"	Under one (1) mile	SF	\$	
		Over one (1) mile	LF	\$	
ο.	8"	90 mils	LF	\$	
).	12"	90 mils	LF	\$	
J.	18"	90 mils	LF	\$	
	24"	90 mils	LF	•	

SUBTOTAL SECTION II:

III. REMOVAL OF PAINT OR THERMOPLASTIC MARKINGS

1. Contractor to provide labor, equipment and materials for the removal of pavement markings from various roadways to include edge lines, centerlines, bike paths and symbols.

a.	Paint	SF	\$
b.	Thermoplastic		
	60 mils	SF	\$
	90 mils	SF	\$

SUBTOTAL SECTION III	II: \$

IV. Raised Pavement Markers (RPMs)

1. Contractor to provide labor, equipment, materials and required maintenance of traffic for the installation of raised pavement markers.

	A. Permanent RPMs, raised, reflectorized. Maximum width 5" Mono-directional with one reflective face, one-color reflectors shall be available as Amber (Yellow), Crystal (White), or Red in the following quantities per Work Order:					
a.	Less than 200	EAC H	\$			
b.	200 to 500	EAC H	\$			
C.	201 to 500	EAC H	\$			
d.	Greater than 1,000	EAC H	\$			

	B. Permanent RPMs, raised reflectorized. Maximum width 5" two-color Bi directional with two reflective faces, which shall be available in Ambe						
			the following quantities per Work Order:				
a.	Less than 200	EAC	\$				
		H					
b.	200 to 500	EAC	\$				
		H					
C.	201 to 500	EAC	\$				
		Н	·				
d.	Greater than 1,000	EAC	\$				
		Н					

2	Removal of existing RPMs at the time of installation of new RPMs	EACH	\$
3	Furnish and Install Ceramic 6" disks with internal reflectors	EACH	\$
4	Furnish and Install traffic delineator pickets	EACH	\$
5	Night/week-end differential	%	\$

SUBTOTAL SECTION IV:	\$